

# SPECIFICATIONS

# 2019 MULE PRO-MX™ EPS



## POWER

Engine	4-stroke, single-cylinder, SOHC, 4-valve, liquid-cooled
Displacement	695cc
Maximum Torque	58 N·m {5.9 kgf·m} / 5,000 min-1
Fuel System	DFI® with 44mm throttle body
Transmission	Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	35.7 amp

## CAPABILITY

Steering	Electric Power Steering (EPS) / rack-and-pinion
Ground Clearance	270mm
Fuel Capacity	36 Litres
Turning Radius	4.2m
Cargo Bed Dimensions (LxWxH)	847 x 1,119 x 232 mm
Cargo Bed Capacity	317kg
Load Capacity	544kg
Seating Capacity	2
Towing Capacity	680kg
Lighting	(2) Halogen (high/low beam) headlights and (2) LED headlights (high/low beam)

## DETAILS

Overall Length	2,795mm
Overall Width	1,525mm
Overall Height	1,890mm
Curb Weight	720kg
Wheelbase	2,005mm
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps
Colour Choices	Timberline Green

\*\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**KAWASAKI.CO.NZ**